

Pneumatiques

	Dimensions	Diamètre (mm)	Largeur (mm)	Charge en Kg par roue	Pression gonflage (en bar)
ROUTIER	(15 x 22.5) 385-65 x 22.5	1 090	380	4 125	5.00
	(16.5 x 22.5) 425-65 x 22.5	1 150	420	5 150	5.00
	(18 x 22.5) 445-65 x 22.5	1 180	440	5 600	5.00
BASSE PRESSION	550/70 x 23 radial	1 330	530	7 000	4.00
	550/45 x 22.5 12P	1 067	550	4590	2.90
	600/50 x 22.5 12P	1150	600	5 200	2.70
	560/60 R 22.5	1 230	550	5 600	2.90
	525/65 R 20.5 XS	1231	557	4815	3.00
	550/60 x 22.5 16P	1 238	550	5 385	2.80
	600/55 x 22.5	1265	600	6770	2.60
	580/65 R 22.5	1300	580	6000	2.80
	600/55 x 26.5	1333	591	6840	2.70
	600/55 R 26,5	1348	626	6930	3.00
	650/55 R 26.5	1360	640	6000	3.50
	620/55 B 26.5 MPT 421	1360	630	5500	4.00
	24 R 20,5 XS	1392	604	7310	3.00
	680/55 R 26.5	1400	680	7000	2.70
	600/60 x 30.5	1500	600	5675	2.00
	700/50 x 30.5 423	1500	700	7030	2.20
	650/65 R 26.5	1518	650	8150	2.80
	620/60 x 30.5 MPT 421	1530	630	5600	3.60
	750/50 x 30.5 MPT 423	1530	750	6500	3.60
	650/65 R 30.5	1600	650	9780	3.20